



**13310
(Fuse-holder)**

Designation : Connecting Lockable Retractable Sleeve 4 mm Banana Tip Fused IP2X Probe Body to Straight 4 mm Banana (male) Plug Lead.



Pulling the top clear button unlocks and retracts the clear sleeve to use the tip. When released the clear sleeve is locked and offers an IP2X touch-proof protection. While the sleeve is released the tip can connect to 4 mm banana sockets like a true safety 4 mm banana plug.



The design and the material of the lantern contact springs meet the need of low resistance and reliability.

European Union marking. The lead complies with the European LVD by meeting the harmonized standard EN / IEC 61010-031:2008.

Electro-PJP's marking. (French design and manufacturing.)

Voltage protection markings.

PVC 0.75 mm² wire. Double jacket wire to offer a wire wear indicator. Usual lengths 100 cm, 200 cm, 300 cm (visible length of the wire, not the overall length of the lead).


The wire attachments comply with heavy duty.

The 4 mm banana male connections comply with the 4 mm banana sockets of most of the worldwide most famous manufacturers and meet the requirements of interchangeability dimensions of the French standard NF C 93-440:1986.

Insulating gray tips on the 4 mm banana male connections to prevent accidental contact.

13310 (Fuse-holder)

Designation : Connecting Lockable Retractable Sleeve 4 mm Banana Tip Fused IP2X Probe Body to Straight 4 mm Banana (male) Plug Lead.

Electrical protection	According to EN / IEC 61010-031:2008. 1000 V CAT II, reinforced insulation, 12 A (fused) (at +40 °C). According to EN / IEC 60529. IP2X (touchproof). These specifications come from the creepage distances, clearances, accessible parts, and solid insulation of the lead. And the considered specifications of the environment are : <ul style="list-style-type: none"> • pollution degree, 1 or 2 or 3 ; • relative humidity, 80 % maximum for temperatures up to 31 °C decreasing linearly to 50 % relative humidity at +40 °C ; • temperature range, +5 °C to +40 °C ; • indoor use ; and • altitude, 2000 m maximum.
	<div style="background-color: #0056b3; color: white; padding: 2px; display: inline-block;">1000 V CAT II</div>
	
Operating temperature range	-20 °C mini., +80 °C maxi. (please see above too).
Protection against fire	Never exceed 12 amperes. The fuse protects the equipment against short-circuits and not against currents slightly higher than usual. Like with any electrical accessory, be especially careful to prevent any increase of current above 12 A. According to EN / IEC 61010-031:2008. It is compatible with the requirements of protection against the spread of fire and resistance to heat by its basic insulation.
Conformity	<ul style="list-style-type: none"> • European Directive "Low Voltage Directive" 2006/95/EC. • International / European standard EN / IEC 61010-031:2008. • International / European standard EN / IEC 60529. • European Directive "RoHS" 2011/65/EU. • European REACH regulation n°1907 / 2006. • French standard NF C 93-440:1986.
Environment	<ul style="list-style-type: none"> • "RoHS" compliant, Pb ≤ 4 % in conductor, Pb ≤ 0.1 % in insulator, Hg ≤ 0.1 %, Cr VI ≤ 0.1 %, Cd ≤ 0.01 %, PBB ≤ 0.1 %, and PBDE ≤ 0.1 %. • REACH compliant, no substances from the candidate list of SVHC for authorisation at mass concentrations greater than 0.1 %.
Materials	Conductors : nickel-coated brass and tinned steel. Wire jackets : PVC or silicone. Insulators and lantern contact spring, please contact us.
Colors	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="background-color: black; color: white; padding: 2px 5px;">Black</div> <div style="background-color: red; color: white; padding: 2px 5px;">Red</div> <div style="background-color: yellow; color: black; padding: 2px 5px;">Yellow</div> <div style="background-color: green; color: white; padding: 2px 5px;">Green</div> <div style="background-color: blue; color: white; padding: 2px 5px;">Blue</div> <div style="background-color: white; color: black; padding: 2px 5px;">White</div> <div style="background-color: brown; color: white; padding: 2px 5px;">Brown</div> </div>
Lengths	100 cm, 200 cm, 300 cm.
Origin	<div style="display: flex; align-items: center; justify-content: center;"> <div style="width: 10px; height: 10px; background-color: blue; margin-right: 5px;"></div> <div style="width: 10px; height: 10px; background-color: red; margin-right: 5px;"></div> Designed and manufactured in France. </div>
Reliability benchmark	Year of 1st placing on the market 2013.

Configure your lead and contact us

Electro-PJP 13310 Series :

- Wire jackets, silicone ? or PVC ?

- Color,
 black ?
 red ?
 yellow ?
 green ?
 blue ?
 brown ? or
 white ?
 (contact us for other colors)

- Length,
 100 cm ?
 200 cm ? or
 300 cm ?
 (contact us for other lengths)

- Fuse,
 0.5 A 1000 V 50 kA ?
 1.0 A 1000 V 50 kA ?
 1.6 A 1000 V 50 kA ?
 2.0 A 1000 V 30 kA ?
 no fuse, empty fuse-holder ?

Contact us at :
 sales@electro-pjp.com

+33(0) 384 821 330

ELECTRO-PJP
 ZI "LES CHARMES D'AMONT"
 13 RUE DE MADRID
 39500 TAVAUX
 FRANCE

GLOSSARY :

ACCESSIBLE. Able to be touched with a standard test finger or test pin.

BASIC INSULATION. Insulation of hazardous live parts which provides basic protection.

CAT II. Measurement or overvoltage category II. For measurement performed on / equipment connected to the building wiring.

CAT III. Measurement or overvoltage category III. For measurement performed on / equipment connected to part of a building wiring installation.

CAT IV. Measurement or overvoltage category IV. For measurement performed on / equipment connected to the origin of the electrical supply to a building.

CLEARANCE. Shortest distance in air between two conductive parts.

CREEPAGE DISTANCE. Shortest distance along the surface of a solid insulating material between two conductive parts.

DOUBLE INSULATION. Insulation comprising both BASIC INSULATION and SUPPLEMENTARY INSULATION.

EN / IEC 60529:2001. The 2001 version of the European / international standard regarding the degrees of protection provided by enclosures.

EN / IEC 61010-031:2008. The latest version (in February 2012) of the European / international standard regarding the safety requirements for electrical equipment for measurement, control and laboratory use – Part 031: Safety requirements for hand-held probe assemblies for electrical measurement and test. Version year 2008.

IP2X. Solid protection to prevent finger touch according to the European / international standard EN / IEC 60529.

"LVD". European Directive 2006/95/EC on the harmonisation of the laws of Member States relating to electrical equipment designed for use within certain voltage limits. (Usually called the Low Voltage Directive.)

NF C 93-440:1986. French standard regarding one pole plugs, sockets and safety assemblies diameter 4 mm and specially the interchangeability dimensions of plugs and sockets.

OVERVOLTAGE CATEGORY. Numeral defining a TRANSIENT OVERVOLTAGE condition.

POLLUTION. Addition of foreign matter, solid, liquid or gaseous (ionized gases), that may produce a reduction of dielectric strength or surface resistivity.

POLLUTION DEGREE. Numeral indicating the level of POLLUTION that may be present in the environment.

POLLUTION DEGREE 1. No POLLUTION or only dry, non-conductive POLLUTION occurs, which has no influence.

POLLUTION DEGREE 2. Only non-conductive POLLUTION occurs except that occasionally a temporary conductivity caused by condensation is expected.

POLLUTION DEGREE 3. Conductive POLLUTION occurs, or dry, non-conductive pollution occurs which becomes conductive due to condensation which is expected.

REINFORCED INSULATION. Insulation which provides protection against electric shock not less than that provided by DOUBLE INSULATION.

"RoHS". European Directive 2002/95/EC on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

SOLID INSULATION. Insulating materials.

SUPPLEMENTARY INSULATION. Independent insulation applied in addition to BASIC INSULATION in order to provide protection against electric shock in the event of a failure of BASIC INSULATION.

TRANSIENT OVERVOLTAGE. Short duration overvoltage of a few milliseconds or less, oscillatory or non-oscillatory, usually highly damped.